



DH15W10 SERIES 15 WATT 10:1 INPUT ISOLATED DC-DC CONVERTER

Features

- Efficiency Up to 86%
- Regulated Outputs
- Fully Protected (OCP/OVP/UVLO)
- 4000Vac I/O Isolation
- Operating Temperature -40 to +80°C
- UL 1741, CSA-C22.2 No.107.1, EN62109-1 Approval
- Shock & Vibration MIL-STD-810F Compliant
- 5000m Operating Altitude
- Input Reverse Polarity Protection



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		% EFF. (1)	CAPACITOR LOAD MAX.
			MIN.	MAX.	NO LOAD	FULL LOAD		
DH15W10-800S05	150-1500 VDC	5 VDC	0 mA	2.00 A	0.5 mA	17 mA	73.5	2000uF
DH15W10-800S12	150-1500 VDC	12 VDC	0 mA	1.25 A	0.5 mA	23 mA	81.5	1250uF
DH15W10-800S15	150-1500 VDC	15 VDC	0 mA	1.00 A	0.5 mA	23 mA	83	1000uF
DH15W10-800S24	150-1500 VDC	24 VDC	0 mA	0.625 A	0.5 mA	22 mA	86	625uF

NOTE:

1. Nominal Input Voltage 800 V_{dc}.
2. Measured at Nominal Input Voltage.

PART NUMBER

Series	Nominal Input Voltage	Number of Outputs	Nominal Output Voltage	Installation Type
DH15W10-	II	O	XX	-Y
DH15W10	800 : 800 VDC	S : Single	05 : 05VDC 12 : 15 : 24 : 24VDC	P : PCB Mount

Part Number Example:

DH15W10-800S12P: 15W, 10:1 150-1500Vdc Input, Single 12Vdc Output, PCB Mounting



DH15W10 Series

TECHNICAL SPECIFICATIONS

			Typ.	Max.	Units	
Input Voltage	Continuous	All	-1500	800	1500	V _{dc}
Operating Temperature	With de-rating, above 50°C	All	-40		80	°C
Storage Temperature		All	-40		85	°C

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Operating Input Voltage		All	150	800	1500	V _{dc}
Turn-On Voltage Threshold	Full load	All	125	140	147	V _{dc}
Turn-Off Voltage Threshold	Full load	All	112	130	137	V _{dc}
Lockout Hysteresis Voltage	Full load	All		10		V _{dc}
Maximum Input Current	V _{in} =150V, Full load	5Vo Others		0.088 0.12		A
No-Load Input Current	V _{in} =800V, I _o =0A	See Model Number Table				mA
Input Filter	Capacitive	All				
Inrush Current	V _{in} =800V _{dc} , Cold Start at 25°C	All		65	150	A

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Voltage Set Point Accuracy	V _{in} =800V, Full load, T _c =25°C	All	-2.0		+2.0	%
Load Regulation	Full load to no load	All			±1.0	%
Line Regulation	V _{in} =High line to low line, full load	All			±1.0	%
Temperature Coefficient	T _c =-40°C to 80°C	All			±0.15	%/°C
Peak-to-Peak	Full load, 10uF aluminum capacitor and 0.1uF ceramic capacitor	5Vo 12Vo 15Vo 24Vo			100 120 150 150	mV
Output Current Range	V _{in} = 150 to 1500V	See Model Number Table				A
Over Current Protection	Hiccup mode. Auto recovery	All	110		300	%
Short Circuit Protection		All	Continuous, Auto Recovery			
External Load Capacitance	Full load (Constant resistive load)	See Model Number Table				uF
Over Voltage Protection	IC component to clamp (auto recovery)	5Vo 12Vo 15Vo 24Vo			8 16 19 30	V _{dc}

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
100% Load	V _{in} =800V, Full load	See Model Number Table				%

	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Error Band	75% to 100% of I _{o,max} , step load change	All			±5	%
Recovery Time	d _i /d _t =0.1A/us (within 1% V _{out} nominal)	All			250	us



DH15W10 Series

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
	$V_{in_min.}$ to 10% V_{o_set} , Power up	All		200		ms
Output Voltage Rise Time	10% V_{o_set} to 90% V_{o_set}	All		8		ms

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Isolation Voltage (100% factory Hi-Pot tested @2sec.)	1 Minute; input to output	All			4000	V_{dc}
Isolation Resistance	Input to output	All	100			MΩ
Isolation Capacitance	Input to output	All		1100		pF

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Switching Frequency	Pulse width modulation (PWM) ($V_{in} = 150V_{dc} - 1500V_{dc}$, Full load)	All	25		75.6	KHz

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
MTBF	$I_o = 100\%$ of $I_{o_max.}$; MIL-HDBK - 217F_Notice 1, GB, 25°C	All	300			K hours
Weight		All		170		grams
Case Material	Plastic, PBT, UL 94V-0					
Base Plate Material	Non-Conductive Base					
Potting Material	UL 94V-0					
Pin Material	Base: Copper Plating: Nickel with Matte Tin					
Shock/Vibration	MIL-STD-810F					
Humidity	95% RH max. Non Condensing					
Altitude	5000m Operating altitude, 12000m Transport altitude					
Thermal Shock	MIL-STD-810F					


EMI	Meets EN 55032 Compliant (with external filter)				Class A	
ESD	EN61000-4-2	Level 3: Air ±8kV, Contact ±4kV			Perf. Criteria A	
Radiated Immunity	EN61000-4-3	Level 3: 80~1000MHz, 20V/m			Perf. Criteria A	
Fast Transient	EN61000-4-4	Level 3: On power input port, ±2kV, external input capacitor required			Perf. Criteria A	
Surge	EN61000-4-5	Level 4: Line to line, ±2kV (with external components)			Perf. Criteria A	
Conducted Immunity	EN61000-4-6	Level 3: 0.15~80MHz, 10V			Perf. Criteria A	
Power Frequency Magnetic Field Immunity	EN61000-4-8	50/60Hz, 3A/m (r.m.s.)			Perf. Criteria A	
Application Note Link						DH15W10 Series App Notes
Packaging Information Link						Packaging Information







DH15W10 Series

CHARACTERISTIC CURVE

Power Derating Curve




Performance Data






DH15W10 Series


DH15W10-800S15
Eff Vs Io @25 Deg. C




DH15W10-800S15
Pd Vs Po @25 Deg. C



DH15W10-800S24
Eff Vs Io @25 Deg. C




DH15W10-800S24
Pd Vs Po @25 Deg. C





DH15W10 Series

MECHANICAL SPECIFICATION



All Dimensions in Inches[mm]

Tolerance Inches: x.xx=±0.03, x.xxx=±0.020

Millimeters: x.x=±0.7, x.xx=±0.50

Pin Connection

Pin	Function
1	-Vin
2	+Vin
3	NC
4	-Vout
5	+Vout

Note: Pin Size is $\phi 0.047 \pm 0.004$ Inch [$\phi 1.20 \pm 0.1$ mm]